SPECIFICATION SHEET OF
LED MINI STEP LIGHT





Je Woo Corporation,Ltd.
Dong Sheng Industrial Park, Dong Sheng Village, Chen Jiang Subdistrict office, Zhong Kai High-Tech Development Zone, Hui Zhou City, Guang Dong, P.R.C.
Tel：86-752-312-5585
Fax：86-752-312-5586 / 5587

Product Feature

Product Description

- AC 120V 50/60Hz operation.
- Less than 1W Low consumption.
- LED lifetime L_{70} 50,000 hours.
- LED Color Rendering Index (CRI) ≥ 90.
- LED Color Rendering R9 (red) ≥ 50
- LED color temperature 3000K.
- Horizontal and vertical face plates optional.
- Photocell function optional.
- Dry location and wet location optional.
- Operating temperature -20℃ to 40℃.
- TYPE IC rated for direct contact with insulations.
- Easily installs in a standard single gang switch box.


Applications

- Hallways, entrances, stairways, wall bases, or any application requiring a low profile, recessed fixtures providing safe illumination in dark areas.

Warranty/Listing

- Warranty 3 years.
- UL and cUL listed for dry and wet locations.

Product Dimension



Product Photo



Louver, Vertical Without photocell

Louver, Horizontal Without photocell



Louver, Vertical With photocell

Louver, Horizontal With photocell



Open hole with photocell

Open hole without photocell

Order Guide

Family	LED quantity	LED color	Material of face	Finish of face	Face Shape	Face Direction	Face Color
SL-M-L: Dry location **WSL-M-L:** Wet location	**09:** 9pcs, photocell **12:** 12pcs LED Without photocell	**W:** White, 3000K	**ST:** Normal steel **SS:** Stainless steel	**1:**Brush (for SS) **3:**Paint (for ST)	**L:**Louver **O:**Open Hole	**V:**Vertical **H:**Horizontal	**BA:** Brushed **WH :**White **BK:** Black **BZ: B**rown

Model List and Characteric

No.	Model	Input			Application	LED quantity	Lumen output
		Voltage	Hz	Power			
1	SL-M-L-09W (Louver)	120AC	50/60	0.7W	Dry location	9pcs	9 lm
2	SL-M-L-09W (Open hole)	120AC	50/60	0.7W	Dry location	9pcs	13 lm
3	SL-M-L-12W (Louver)	120AC	50/60	1.0W	Dry location	12pcs	13 lm
4	SL-M-L-12W (Open hole)	120AC	50/60	1.0W	Dry location	12pcs	38 lm
5	WSL-M-L-09W (Louver)	120AC	50/60	0.7W	Wet location	9pcs	9 lm
6	WSL-M-L-09W (Open hole)	120AC	50/60	0.7W	Wet location	9pcs	13 lm
7	WSL-M-L-12W (Louver)	120AC	50/60	1.0W	Wet location	12pcs	13 lm
8	WSL-M-L-12W (Open hole)	120AC	50/60	1.0W	Wet location	12pcs	38 lm

Packaging

